

Camerano, March 2014

Certificate of Conformity

COMBO CABLES MINI HD

We, **ELAN s.r.l.**, **CERTIFY** that the cables marked with:

ELAN COMBO MINI HD LSZH CEI 20-22 III – CEI 20-37 – CEI 36762 C-4
(U₀=400 V) – CE – “production date”

are manufactured in accordance with the Standards indicated below.

MANUFACTURING TECHNICAL FEATURES



1. UNIPOLAR WIRES:

- a. The unipolar wires (1,00 – 1,50) which are the feeding conductors are insulated in PVC type R2. They pass the test of voltage according to CEI 20-20 standard: 5 minutes with 2000 V. in dry current without any crack of insulation covering.
- b. The unipolar wires (0,50) which are the signal conductors are insulated in PVC type R2. They pass the test of voltage according to CEI 20-20 standard: 5 minutes with 2000 V. in dry current without any crack of insulation covering.

2. COAX MINI HD:

Insulation: PE compact – gauge 1,10 mm and diameter 2,9 mm

Jacket: semi-compressed in purple M1 LSZH flame retardant to CEI 20-22 III (IEC60332-3), CEI 36762 and CEI 20-37 standards.

3. JACKET:

The jacket in M21 type black colour and flame retardant to CEI 20-22 III, CEI 36762, CEI 20-37 for indoor and outdoor use (water resistant and UV resistant).

Cables marked as C-4 (U₀=400V) owing to their technical characteristics and the positive results obtained by passing the tests and can be installed with electrical power cables marked both 450/750V, and 0,6/1 Kv according to CEI UNEL 36762 and can be used in outdoor applications.

Elan Srl



CANALE INTERRATO /
BURIED TROUGH



TUBO INTERRATO /
BURIED DUCT



INTERRATO CON
PROTEZIONE /
BURIED WITH
PROTECTION



LOW SMOKE
EMISSION



HALOGEN FREE



ESTERNO /
OUTDOOR



FIRE RETARDANT



CON CAVI Elett.
WITH POWER CABLES