



ELAN s.r.l. - Via Osimana, 70 - 60021 Camerano (AN) - Italy **Tel.** +39.071.7304258 - Fax +39.071.7304282 **Sito Web: www.elan.an.it** - E-mail: info@elan.an.it R.E.A. AN n. 152242 - Cod. Fisc. e Part. IVA IT 01572590428









Cycle service life in relation to depth of discharge 120 100 Capacity (%) 80 60 100% D.O.D. 50% D.O.D. 30% Depth of discharge 40 20 0 200 600 1000 1200 1400 400 800 Number of cycles(cycles)

"Merce non prodotta in UE" - "Goods are not produced in UE"

6V. 12 Ah.





Chara	cterist	tics	
Capacity 25° C (77° F)		20 hour rate (0.60 A) 10 hour rate (1.15 A) 5 hour rate (2.02 A) 1 hour rate (7.80 A)	12.00 AH 11.50 AH 10.10 AH 7.80 AH
		1.5 hour discharge to 5.25V	4.80 A
Internal Resistance		Full charged battery at 25° C (77° F)	9 mΩ
Capacity effected by temperature (20 hour rate)		40° C (104° F) 25° C (77° F) 0° C (32° F) -15° C (5° F)	102 % 100 % 85 % 65 %
Self-discharge at 25° C (77° F)		Capacity after 3 month storage Capacity after 6 month storage Capacity after 12 month storage	91 % 82 % 64 %
Charge (constant voltage)	Cycle	Initial charging currentless than 4.0A Voltage 7.30 – 7.50V.	
	Float	Voltage 6.90 – 7.00V.	

Il costruttore si riserva di apportare modifiche al prodotto senza preavviso - The manufacturer reserves the right to modify the product without notice

l