


ELAN s.r.l. - Via Osimana, 70 - 60021 Camerano (AN) - Italy R.E.A. AN n. 152242 - C. F. e P. IVA IT 01572590428 - Cap. Soc. € 98.940,00 i.v. **Tel.** +39.071.7304258 - Fax +39.071.7304282 Sito Web: www.elan.an.it - E-mail: info@elan.an.it





















Characteristics			
Capacity 25° C (77° F)		10 hour rate (300 A) 5 hour rate (480 A) 1 hour rate (1650 A)	3000 AH 2400 AH 1650 AH
		1.5 hour discharge to 1.75V	1200 A
Internal Resistance		Full charged battery at 25° C (77° F)	1.6 m Ω
Capacity effected by temperature (20 hour rate)		40° C (104° F) 25° C (77° F) 0° C (32° F) -15° C (5° F)	102 % 100 % 85 % 65 %
Self-discharge at 25° C (77° F)		Capacity after 3 month storage Capacity after 6 month storage Capacity after 12 month storage	91 % 82 % 64 %
Charge (constant voltage)	Cycle	Initial charging currentless than 750 A Voltage 2.35 – 2.40V.	
	Float	Voltage 2.25 – 2.30V.	

Il costruttore si riserva di apportare modifiche al prodotto senza preavviso - The manufacturer reserves the right to modify the product without notice